

ANUCOLOR[©] Fast Yellow Y-138

PRODUCTION INFORMATION

ANUCOLOR® Fast Yellow Y 138 is medium shade redder di arylide yellow pigment offering good opacity and tinting strength as compared to other di arylide yellows. This product is especially designed for universal printing ink application.

PRODUCT INFORMATION

Chemical Type	Dis Azo Yellow	
C.I.Name	PY 13	
C.I. No	21100	
CAS NO	5102-83-0	
EINECS /ELINCS No	225-822-9	
PHYSICAL FORM	Free Flowing Powder	

CHEMICAL STRUCTURE

COLOURESTICES / FASTNESS PROPERTIES

TECHNICAL DATA and APPLICATION

FULL TONE (0.2 %	5)	Reduction Tone (1: 20)	
L	85.59	L	93.39
С	92.92	С	52.29
Н	83.39	Н	88.97
a	21.02	а	- 0.59
b	88.49	b	39.98
Light Fastness	6-7	Light Fastness 4-5	
Weather Fastness	2-3	Weather Fastness	1-2

APPLICATION

Aqueous Liquid Ink	Recommended
Solvent Liquid Inks	Recommended
Offset Printing Inks	Recommended

PHYSICAL DATA

Oil Absorption	gm/100gm	40.00-55.0
Bulk Density	Kg/Lt 0.30-0.4	
Specific Gravity	Gm/cm ³	1.20- 1.40
рН	Number	6.00-8.00

HEATING STABILITY

Temperature	Duration	Suitability	
150°C.	20 Min	SB	

SOLVENT RESISTANCE (On 1-5 Grey wool scale)

Water	Alkali	Acid	Ethyl Acetate	Xylene	MEK	IPA
5	5	5	5	4	4	5

STANDARD PACKAGING

20 Kg Plastic Bag

DISCLAIMER: The colour panels and other information provided in the shade card are given in good faith and are to be used as a guide only. Verification under actual conditions is recommended before use.