

ANUCOLOR[©] Lake Red C R 533


PRODUCTION INFORMATION

ANUCOLOR® Lake Red C R 533 is Mono Azo Lake Red economical grade pigment. It exhibits high colour strength, gloss and good solvent resistance properties.

PRODUCT INFORMATION

Chemical Type	Mono Azo Naphthol Red	
C.I.Name	PR53:1	
C.I. No	15585:1	
CAS NO	5160-02-01	
EINECS /ELINCS No	225-935-3	
PHYSICAL FORM Free Flowing Powder		

CHEMICAL STRUCTURE



COLOURESTICES / FASTNESS PROPERTIES

TECHNICAL DATA and APPLICATION

FULL TONE (0.2 %	S)	Reduction Tone (1: 20)		
		Reduction Tone (1: 20)		
	T		Γ	
L	39.36	L	65.24	
С	39.60	С	55.96	
Н	36.20	Н	27.97	
a	33.09	а	49.91	
b	23.13	b	29.93	
Light Fastness	6-7	Light Fastness	1-2	
Weather Fastness	2-3	Weather Fastness	2-3	

APPLICATION

Aqueous Liquid Ink	-
Solvent Liquid Ink	Recommended
Offset Printing Ink	Recommended

PHYSICAL DATA

Oil Absorption	gm/100gm	35.0-50.0
Bulk Density	Kg/Lt	0.30-0.40
Specific Gravity	Gm/cm ³	1.75-1.95
pН	Number	6.00-8.00

HEATING STABILITY

Temperature	Duration	Suitability
150°C.	20 Min	SB

SOLVENT RESISTANCE (On 1-5 Grey wool scale)

Water	Alkali	Acid	Ethyl Acetate	Xylene	MEK	IPA
5	5	5	3	3	3	4

STANDARD PACKAGING

20 Kg Plastic Bag	42"x42" inch Wooden pallet contains 300 Kg Material.
-------------------	--

DISCLAIMER: The colour panels and other information provided in the shade card are given in good faith and are to be used as a guide only. Verification under actual conditions is recommended before use.