

ANURANG Scarlet Chrome S -43

Free Flowing Powder

PRODUCTION INFORMATION

ANURANG Scarlet Chrome S-43 is a pre-darkened Molybdate Orange pigment having bluish mass tone. This is a highly stabilized chrome pigment having clean mass tone and especially designed for Paints & Coatings segment

PRODUCT INFORMATION

PHYSICAL FORM

Chemical Type Molybdate Chrome C.I.Name Pigment Red 104 C.I. No 77605 CAS NO 12656-85-8 EINECS /ELINCS No 235-759-9

APPLICATION PROFILE

Water borne Paints	
Air Drying Alkyds	Recommended
Aqueous Pigment Emulsion	Recommended
Stoving Enamels	Recommended
Powder Coating	
Industrial Coating	Recommended
Coil Coating	

COLOURESTICES / FASTNESS PROPERTIES

TECHNICAL DATA

PHYSICAL DATA

FULL TONE (0.2 %	ś)	Reduction Tone (1: 10)		
L	52.80	L	67.99	
С	71.28	С	46.71	
Н	39.89	Н	31.49	
a	54.91	a	39.85	
b	45.75	b	24.99	
Light Fastness	6-7	Light Fastness	5-6	
Weather Fastness	4-5	Weather Fastness	3-4	

Oil Absorption	gm/100gm	15.0-20.0
Bulk Density	Kg/Lt	1.10-1.30
Specific Gravity	Gm/cm ³	5.00-6.00
Н	Number	6.00-8.00

RESISTANCE TO HEAT

120°C/	150°C/	180°C/	210°C/	-
30 Min.	20 Min.	10 Min.	10 Min.	
SB	SB	SB	USB	-

RESISTANCE TO ACID and ALKALI

ACID	ALKALI
Fair	Poor

BLEEDING PROPERTIES (1-5 Scale, Where 5: No Bleed & 1: Considerable bleed)

Linseed Oil	Ethanol	Ethyl Acetate	Xylene	n-Butanol	M.E.K.	M.T.O.	Cellosolve	D.O.P.	Acetone
5	5	5	5	5	5	5	5	5	5

STANDARD PACKAGING

20 Kg Plastic Bag	1500 Kg Material kept in 42"x42" inch wooden pallet
-------------------	---

<u>DISCLAIMER</u>: The colour panels and other information provided in the shade card is given in good faith and is to be used as a guide only. Verification under actual conditions are recommended before use.