

# ANURANG Scarlet Chrome S-41

### PRODUCTION INFORMATION

**ANURANG Scarlet Chrome S-41** is a Molybdate Orange pigment having yellowish mass tone. This is a highly stabilized chrome pigment having clean mass tone and especially designed for all type of the paints & coatings application

### PRODUCT INFORMATION

### APPLICATION PROFILE

Chemical Type	Molybdate Chrome		
C.I.Name Pigment Red 104			
<b>C.I. No</b> 77605			
CAS NO 12656-85-8			
EINECS /ELINCS No	235-759-9		
PHYSICAL FORM	Free Flowing Powder		

Water borne Paints	Recommended
Air Drying Alkyds	Recommended
Aqueous Pigment Emulsion	Recommended
Stoving Enamels	Recommended
Powder Coating	Recommended
Industrial Coating	Recommended
Coil Coating	

# **COLOURESTICES / FASTNESS PROPERTIES**

# TECHNICAL DATA

PHYSICAL DATA

рΗ

FULL TONE (0.2 %	ś)	Reduction Tone	(1:10)
L	52.70	L	67.90
С	71.38	С	46.41
Н	39.65	Н	31.30
a	54.96	a	39.65
b	45.55	b	24.
Light Fastness	6-7	Light Fastness	5-6
Weather	4-5	Weather	3-4
Fastness		Fastness	

Oil Absorption	gm/100gm	15.0-20.0
Bulk Density	Kg/Lt	1.10-1.30
Specific Gravity	Gm/cm <sup>3</sup>	5.00-6.00

Number

6.00-8.00

#### **RESISTANCE TO HEAT**

120°C/	150°C/	180°C/	210°C/	-
30 Min.	20 Min.	10 Min.	10 Min.	
SB	SB	SB	SB	-

### **RESISTANCE TO ACID and ALKALI**

ACID	ALKALI
Fair	Poor

## BLEEDING PROPERTIES (1-5 Scale, Where 5: No Bleed & 1: Considerable bleed)

Linseed Oil	Ethanol	Ethyl Acetate	Xylene	n-Butanol	M.E.K.	M.T.O.	Cellosolve	D.O.P.	Acetone
5	5	5	5	5	5	5	5	5	5

## STANDARD PACKAGING

20 Kg Plastic Bag	1500 Kg Material kept in 42"x42" inch wooden pallet
-------------------	---

<u>DISCLAIMER</u>: The colour panels and other information provided in the shade card is given in good faith and is to be used as a guide only. Verification under actual conditions are recommended before use.